



## RM-E Rooster magneten

Ontijzeringsysteem voor de voedingsmiddelen industrie



**Bakker Magnetics**

Always ahead.

## Datasheet Bakker Magnetics

### RM-E Rooster magneten

**versie 1.0**

- Uitvoering : Rooster magneet type RM-E (/EC)  
Volgens de FDA en EHEDG richtlijnen  
Robuuste constructie  
Permanent magnetisch  
Waterdicht
- Behuizing : Roestvrij staal 1.4404
- Oppervlakte behandeling : Gepolijst
- Magneet specificaties : Permanente neodymium magneten,  
kwaliteit: BM40M

#### Tevens beschikbaar:

- Easy clean versie (RM-E/EC)
- Rond; standaard of easy clean uitvoering.

#### **Standaard versie (RM-E)**

Artikel nummer	A	B	# Staven	Gewicht (kg)
25.400/01	96	96	1	0,5
25.401/01	146	146	2	1,1
25.402/01	196	196	3	1,9
25.403/01	246	246	4	3,5
25.404/01	296	296	5	5,6
25.405/01	346	346	6	8,2
25.406/01	396	396	7	11,3
25.407/01	446	446	8	14,9
25.408/01	496	496	9	18,9
25.409/01	546	546	10	23,3
25.410/01	596	596	11	29,7
25.411/01	696	696	13	37,1
25.412/01	796	796	15	46,5
25.420/01	96	96	2	0,7
25.421/01	146	146	3	1,3
25.422/01	196	196	4	2,3
25.423/01	246	246	5	4,2
25.424/01	296	296	6	6,5
25.425/01	346	346	7	9,4
25.426/01	396	396	8	12,7
25.427/01	446	446	9	16,5
25.428/01	496	496	10	20,5
25.429/01	546	546	11	26,4
25.430/01	596	596	12	32,1
25.431/01	696	696	14	40,1
25.432/01	796	796	16	49,4

Alle afmetingen (in mm) zoals afgebeeld in de tekening op de laatste pagina.



**Bakker Magnetics**

Always ahead.

**Easy clean versie (RM-E/EC)**

Artikel nummer	A	B	# Staven	Gewicht (kg)
25.440/01	96	96	1	0,7
25.441/01	146	146	2	1,3
25.442/01	196	196	3	2,3
25.443/01	246	246	4	4,0
25.444/01	296	296	5	6,2
25.445/01	346	346	6	8,8
25.446/01	396	396	7	12,1
25.447/01	446	446	8	15,7
25.448/01	496	496	9	19,9
25.449/01	546	546	10	24,3
25.450/01	596	596	11	31,7
25.451/01	696	696	13	39,1
25.452/01	796	796	15	47,5
25.460/01	96	96	2	0,9
25.461/01	146	146	3	1,5
25.462/01	196	196	4	2,7
25.463/01	246	246	5	4,6
25.464/01	296	296	6	7,1
25.465/01	346	346	7	9,9
25.466/01	396	396	8	13,4
25.467/01	446	446	9	17,3
25.468/01	496	496	10	21,8
25.469/01	546	546	11	26,4
25.470/01	596	596	12	34,1
25.471/01	696	696	14	42,3
25.472/01	796	796	16	50,9

Alle afmetingen (in mm) zoals afgebeeld in de tekening op de laatste pagina.



**Bakker Magnetics**

Always ahead.

Voor meer informatie of vragen kunt u contact met ons opnemen:

**Bakker Magnetics**

Sciencepark Eindhoven 5502  
5692 EL Son, The Netherlands

Afdeling : Magnetic Separation Technology

Telefoon: +31 (0) 40 2 678 840

E-Mail : [mst@baktermagnetics.com](mailto:mst@baktermagnetics.com)

*Dimensions and shape of the magnet, in combination with required manufacturing processes, may cause the magnetic and physical characteristics to vary from typical values. Therefore, all data presented in this document are for general reference only and should not be relied upon to represent standard characteristics, nor are they guaranteed upon use. Bakker Magnetics reserves the right to change information in this document, including magnet performance standards, specifications, and characteristics without notice.*



Always ahead.

