



RRM/EC Ronde rooster magneten

Scheidingsystemen voor diverse industrieën



Bakker Magnetics

Always ahead.

Datasheet Bakker Magnetics

RRM/EC Ronde rooster magneten

versie 1.0

- Uitvoering : Ronde rooster magneet easy clean type RRM/EC
Robuuste constructie
Permanent magnetisch
Uitgevoerd met Jacob flens aansluiting
- Behuizing : Roestvrij staal 1.4301
- Oppervlakte behandeling : Gestraald
- Magneet specificaties : Permanente neodymium magneten
25.120/01 – 25.124/01: kwaliteit BM48H
25.126/01 – 25.128/01: kwaliteit BM40H

Standaard versie (RRM/EC)

Artikel nummer	A ∅	B	C	# Staven	Gewicht (kg)
25.120/01	100	50	80	2	1,5
25.121/01	150	50	120	3	3,0
25.122/01	200	50	120	4	4,0
25.123/01	250	50	120	5	5,5
25.124/01	300	50	120	6	7,0
25.126/01	400	55	2 x 120	8	9,0
25.128/01	500	55	2 x 120	10	11,5

Alle afmetingen (in mm) zoals afgebeeld in de tekening op de laatste pagina.



Bakker Magnetics

Always ahead.

Voor meer informatie of vragen kunt u contact met ons opnemen:

Bakker Magnetics

Sciencepark Eindhoven 5502
5692 EL Son, The Netherlands

Afdeling : Magnetic Separation Technology
Telefoon : +31 (0) 40 2 678 840
E-Mail : mst@bakkermagnetics.com

Dimensions and shape of the magnet, in combination with required manufacturing processes, may cause the magnetic and physical characteristics to vary from typical values. Therefore, all data presented in this document are for general reference only and should not be relied upon to represent standard characteristics, nor are they guaranteed upon use. Bakker Magnetics reserves the right to change information in this document, including magnet performance standards, specifications, and characteristics without notice.



Always ahead.

