

## BAXX THE POWERLIFTER | PRODUCTLIST 2015

ISO 9001 and ISO 14001 Certified  
Version 1.0

### Powerful Permanent Lifting Magnets

Type	Art.no	Weight
BAXX 125	50.650	3 KG
BAXX 250	50.651	10 KG
BAXX 500	50.652	20 KG
BAXX 1000	50.653	40 KG
BAXX 2000	50.654	90 KG



### List of replacement parts and part numbers

	Load eye	Lever and handle	Locking assembly	Grip
BAXX 125	50.650/90	50.650/91	50.650/92	50.650/94
BAXX 250	50.650/90	50.651/91	50.650/92	50.653/94
BAXX 500	50.652/90	50.652/91	50.650/92	50.653/94
BAXX 1000	50.652/90	50.653/91	50.650/92	50.653/94
BAXX 2000	50.654/90	50.654/91	50.654/92	50.654/94

### Baxx 125

Traction force [kg]	0 [mm]	0.1 [mm]	0.3 [mm]	0.5 [mm]
Flat 60 [mm]	125	110	70	60
Flat 20 [mm]	125	100	70	60
Flat 15 [mm]	125	100	70	60
Flat 10 [mm]	110	90	65	55
Flat 5 [mm]	55	50	45	40
Flat 4 [mm]	40	40	35	30
Round bar 180 [mm]	x	X	X	x
Round bar 60 [mm]	60	50	45	35

#### IMPORTANT NOTICE

Published information concerning Bakker Magnetics products is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of Bakker Magnetics products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice. Bakker Magnetics 2015.

## Baxx 250

Traction force [kg]	0 [mm]	0.1 [mm]	0.3 [mm]	0.5 [mm]
Flat 60 [mm]	250	225	200	130
Flat 20 [mm]	250	225	200	130
Flat 15 [mm]	250	225	200	130
Flat 10 [mm]	200	175	140	110
Flat 5 [mm]	60	55	55	50
Flat 4 [mm]	50	45	40	40
Round bar 180 [mm]	200	175	140	110
Round bar 120 [mm]	125	115	75	55
Round bar 60 [mm]	95	90	70	55

## Baxx 500

Traction force [kg]	0 [mm]	0.1 [mm]	0.3 [mm]	0.5 [mm]
Flat 60 [mm]	500	500	325	260
Flat 20 [mm]	500	400	310	240
Flat 15 [mm]	350	300	275	225
Flat 10 [mm]	275	225	200	170
Flat 5 [mm]	70	65	60	60
Flat 4 [mm]	55	55	50	45
Round bar 240 [mm]	260	240	150	95
Round bar 180 [mm]	350	350	320	235
Round bar 120 [mm]	290	265	205	145
Round bar 60 [mm]	175	165	150	120

## Baxx 1000

Traction force [kg]	0 [mm]	0.1 [mm]	0.3 [mm]	0.5 [mm]
Flat 60 [mm]	1000	1000	900	800
Flat 20 [mm]	700	700	600	450
Flat 15 [mm]	575	575	400	325
Flat 10 [mm]	400	400	300	275
Round bar 300 [mm]	620	615	545	465
Round bar 240 [mm]	660	635	560	475
Round bar 180 [mm]	700	700	600	550
Round bar 120 [mm]	395	365	325	295
Round bar 60 [mm]	250	250	225	200

### IMPORTANT NOTICE

Published information concerning Bakker Magnetics products is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of Bakker Magnetics products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice. Bakker Magnetics 2015.

## Baxx 2000

Traction force [kg]	0 [mm]	0.1 [mm]	0.3 [mm]	0.5 [mm]
Flat 60 [mm]	2000	2000	1700	1200
Flat 20 [mm]	1000	925	825	700
Flat 15 [mm]	750	750	600	600
Round bar 300 [mm]	1090	1075	995	855
Round bar 240 [mm]	1125	1090	1005	900
Round bar 180 [mm]	1100	1100	1000	950
Round bar 120 [mm]	635	600	590	565

### IMPORTANT NOTICE

Published information concerning Bakker Magnetics products is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of Bakker Magnetics products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to change without prior notice. Bakker Magnetics 2015.